



Monterey Grey



Azurite Blue

SPECIFICATIONS

Frame	6061 aluminum triple gauge main tubes with hydro-formed top tube, sloping design for men's, step through design for ladies, center-mount kickstand plate, replaceable derailleur hanger, eyeleted dropouts, Alloy Kickstand
Fork	RST Neon-T suspension fork, coil spring with external preload adjustment, 60mm travel
Headset	Water-resistant sealed mechanism, threaded, 1 1/8"
Wheels	Weinmann ZAC-19 double wall alloy rims, 32H, Formula alloy hubs with QR and 14g stainless steel spokes
Tires	CST Marathon/Tour with silver safety stripe, 700 x 38c
Derailleurs	Shimano Altus RD-M310 rear and Shimano FD-M191 front, 31.8mm clamp, top swing/dual pull front
Shiftlevers	Shimano EZ-FIRE PLUS window type, ST-EF51, 21-Speed
Chain	KMC UG51, 7-Speed
Cassette	Shimano MF-TZ31 7-Speed, 14-34T
Crankset	Shimano FC-M171 triple, 48/38/28T, 170mm with chainguard
BB Set	VP sealed cartridge, 68 x 122.5mm
Pedals	Comfort platform style with TPE non-slip insert
Brakeset	Forged alloy linear-pull brakes with front power modulator and Shimano brake levers
Handlebar	Comfort hi-rise, steel, 25.4 x 80mm rise x 15° sweep x 640mm
Stem	Jamis alloy angle-adjustable, 90mm with 150mm quill (14-17"), 110mm with 180mm quill (18-23")
Grips	New anatomic triple density kraton grip with reflective end plug
Seat Post	Suspension alloy micro-adjust, 27.2 x 350mm with alloy clamp and QR seatpin. 300mm for Men's 15, 17, Step-Thru 14
Saddle	Jamis Comfort with memory foam, synthetic suede cover, burnished sides and bumper springs with satin steel rails, gender specific
Sizes	M: 15", 17", 19", 21", 23" S/T: 14", 18"
Color	M: Azurite Blue or Monterey Grey S/T: Misty Green or Azurite Blue

UPGRADES/CHANGES FROM 2014

- Lightwheel 32H wheel build
- Jamis 35° quill stem
- New Anatomic grip with reflective end plug
- Alloy Kickstand

REASONS TO UPGRADE FROM CITIZEN 1

- Lightweight aluminum frame
- RST Neon-T suspension fork, coil spring with external preload adjustment, 60mm travel
- Shimano FC-M171 crankset
- Weinmann lightweight 32H double wall rims
- Shimano ST-EF51 EZ-FIRE PLUS window type shifters and Altus rear derailleur
- Jamis Comfort Memory foam saddle
- Suspension alloy micro-adjust seat post

TOP 5 THINGS YOU NEED TO KNOW

- SR/Suntour M3010AL suspension fork offers 2" (50mm) of coil-sprung suspension, a lightweight alloy crown and lowers, and preload adjuster to dial-in the stiffness of the suspension according to rider weight & preference.
- The Shimano 21-speed Revo EZ-Fire shifting drivetrain with Shimano M171 48/38/28 crankset, Altus front and front derailleurs and 14-34 Mega-Range freewheel offers a much larger gear range, with much lower gearing, for easier hill climbing than standard or compact double chainring road and street bikes.
- Weinmann's ZAC-19 double wall rims are stronger, lighter and longer lasting than standard single wall rims.
- Our super plush saddle features memory foam padding for optimum support with maximum comfort. The slip-resistant suede-type top prevents sliding and the burnished side panels reduce leg friction while pedaling. With elastomer springs to help soak up road vibrations.
- TPE slip-resistant, shock-absorbing inserts on finger & foot contact points on both brake levers and pedals help Citizen deliver a comfortable and secure workout.

GEOMETRY

SIZE	CENTER of BB to TOP of TT	EFFECTIVE TT LENGTH	HT ANGLE	ST ANGLE	CHAINSTAY	WHEELBASE	FORK RAKE	BB HEIGHT	HEADTUBE	STANDOVER
15	13.42/341	21.50/546	70°	74°	17.52/445	41.69/1059	1.97/50	11.22/285	4.72/120	28.66/728
17	15.04/382	22.11/562	70°	74°	17.52/445	42.28/1074	1.97/50	11.22/285	4.72/120	29.05/738
19	17.24/438	22.48/571	71°	73.5°	17.52/445	42.05/1068	1.97/50	11.22/285	4.72/120	30.39/772
21	19.29/490	23.06/586	71°	73.5°	17.52/445	42.68/1084	1.97/50	11.22/285	5.12/130	31.65/804
23	20.82/529	23.46/596	71°	73.5°	17.52/445	43.07/1094	1.97/50	11.22/285	5.71/145	32.91/836
14 S/T	5.59/142	21.49/546	70°	74°	17.52/445	41.77/1061	1.97/50	11.22/285	5.90/150	18.62/473
18 S/T	5.90/150	21.88/556	70°	73.5°	17.52/445	41.97/1066	1.97/50	11.22/285	6.49/165	18.15/461